

# Surface Magnet

Magnets that attach to the base of the accelerometer for route-based data collection and roving measurements.

## Features

Adhesive mounting pads, magnets, spotface tools, mounting studs, motor fin mounts, probe tips and epoxy are all tools used in the installation of industrial accelerometers. For questions on what accessory will work best with your vibration sensor please call our toll free number or send us an email.

## Protecting






For use in Fans, Motors, Pumps, Compressors, Centrifuges, Conveyors, Air Handlers, Gearboxes, Rolls, Dryers, Presses, Cooling, HVAC, Spindles, Machine Tooling, Process Equipment and many more.

Model	Product	Description
CM-080A120	 Flat Surface Magnet	Flat surface magnet with mounting stud <ul style="list-style-type: none"> <li>• Size - Diameter: 0.75 in (19.05 mm)</li> <li>• Pull Strength: 15 lb (67 N)</li> <li>• Mounting Thread: 1/4-28 Female</li> </ul>
CM-080A121	 Flat Surface Magnet	Flat surface magnet with mounting stud <ul style="list-style-type: none"> <li>• Diameter: 1.0 in (25.4 mm)</li> <li>• Pull Strength: 35 lb (156 N)</li> <li>• Mounting Thread: 1/4-28 Female.</li> </ul>
CM-080A122	 Flat Surface Magnet	Flat surface magnet with mounting stud <ul style="list-style-type: none"> <li>• Diameter: 1.5 in (38 mm)</li> <li>• Pull Strength: 50 lb (222 N)</li> <li>• Mounting Thread: 1/4-28 Female</li> </ul>
CM-M080A120	 Flat Surface Magnet	Flat surface magnet with mounting stud <ul style="list-style-type: none"> <li>• Diameter: 0.75 in (19.05 mm)</li> <li>• Pull Strength: 15.16 lb (67 N)</li> <li>• Mounting Thread: M6x1 Female</li> </ul>
CM-M080A121	 Flat Surface Magnet	Flat surface magnet with mounting stud <ul style="list-style-type: none"> <li>• Diameter: 1.0 in (25.4 mm)</li> <li>• Pull Strength: 35 lb (156 N)</li> <li>• Mounting Thread: M6x1 Female</li> </ul>
CM-M080A122	 Flat Surface Magnet	Flat surface magnet with mounting stud <ul style="list-style-type: none"> <li>• Diameter: 1.5 in (38 mm)</li> <li>• Pull Strength: 50 lb (222 N)</li> <li>• Mounting Thread: M6x1 Female</li> </ul>
CM-080A130	 Curved Surface Magnet	Curved surface magnet with mounting stud <ul style="list-style-type: none"> <li>• Size - Diameter: 0.75 in (19.05 mm)</li> <li>• Pull Strength: 15 lb (67 N)</li> <li>• Mounting Thread: 1/4-28 Female</li> </ul>
CM-080A131	 Curved Surface Magnet	Curved surface magnet with mounting stud <ul style="list-style-type: none"> <li>• Size - Diameter: 1.0 in (25.4 mm)</li> <li>• Pull Strength: 35 lb (156 N)</li> <li>• Mounting Thread: 1/4-28 Female</li> </ul>
CM-080A132	 Curved Surface Magnet	Curved surface magnet with mounting stud <ul style="list-style-type: none"> <li>• Size - Diameter: 1.5 in (38 mm)</li> <li>• Pull Strength: 55 lb (245 N)</li> <li>• Mounting Thread: 1/4-28 Female</li> </ul>



SEC of America  
 807 E Main St. Durham, NC 27701.  
 Ph: (919) 533-4920  
 sales@sec-america.com  
 www.sec-america.com



Model	Product	Description
CM-080A133	 Curved Surface Magnet	Curved surface magnet with mounting stud <ul style="list-style-type: none"> <li>• Size - Diameter: 2.0 in (52 mm)</li> <li>• Pull Strength: 85 lb (378 N)</li> <li>• Mounting Thread: 1/4-28 Female</li> </ul>
CM-M080A130	 Curved Surface Magnet	Curved surface magnet with mounting stud <ul style="list-style-type: none"> <li>• Size - Diameter: 0.75 in (19 .05mm)</li> <li>• Pull Strength: 15 lb (67N)</li> <li>• Mounting Thread: M6x1 Female</li> </ul>
CM-M080A131	 Curved Surface Magnet	Curved surface magnet with mounting stud <ul style="list-style-type: none"> <li>• Size - Diameter: 1 in ( 25.4 mm)</li> <li>• Pull Strength: 15 lb (67N)</li> <li>• Mounting Thread: M6x1 Female</li> </ul>
CM-M080A132	 Curved Surface Magnet	Curved surface magnet with mounting stud <ul style="list-style-type: none"> <li>• Size - Diameter: 1.5 in ( 38 mm)</li> <li>• Pull Strength: 55 lb (245 N)</li> <li>• Mounting Thread: M6x1 Female</li> </ul>
CM-M080A133	 Curved Surface Magnet	Curved surface magnet with mounting stud <ul style="list-style-type: none"> <li>• Size - Diameter: 2 in ( 50.8 mm)</li> <li>• Pull Strength: 85 lb (378 N)</li> <li>• Mounting Thread: M6x1 Female</li> </ul>



SEC of America  
807 E Main St. Durham, NC 27701.  
Ph: (919) 533-4920  
sales@sec-america.com  
www.sec-america.com

